

Pozytyw

S320 GD

t	q	J _{y,brutto}	A _{brutto}	A _{eff}	i _{y,brutto}	N _{cR}	W _{min}	Z _{max}	W _{max}	V _R	R _{Rd,A}	R _{Rd,B,60}	R _{Rd,B,200}
mm	kg/m ²	cm ⁴ /m	cm ² /m		cm	kN/m	cm ³ /m	mm	cm ³ /m	kN/m			
0.70	11.43	467.82	14.56	6.13	5.67	196.19	47.25	78.53	48.56	32.47	7.14	24.97	39.90
0.75	12.25	501.24	15.60	6.87	5.67	219.74	51.84	79.46	54.57	39.51	8.27	28.72	45.72
0.80	12.92	534.65	16.46	7.63	5.70	244.13	56.31	80.24	60.48	47.48	9.48	32.70	51.88
0.88	14.37	588.12	18.31	8.90	5.67	284.74	63.86	80.91	69.78	62.31	11.57	39.51	62.36
0.90	14.70	601.48	18.72	9.21	5.67	294.59	65.70	81.00	71.97	66.44	12.12	41.29	65.08
1.00	16.33	668.31	20.80	10.62	5.67	339.84	74.76	81.37	82.68	89.78	15.06	50.73	79.50
1.15	18.78	768.56	23.92	12.82	5.67	410.30	88.86	81.88	99.57	133.97	20.02	66.43	103.26
1.25	20.41	835.39	26.00	14.46	5.67	462.69	98.43	81.88	110.30	170.17	23.70	77.94	120.55
1.50	24.50	1002.47	31.20	19.18	5.67	613.79	122.46	81.88	137.23	251.00	34.14	110.05	168.34

Negatyw

S320 GD

t	q	J _{y,brutto}	A _{brutto}	A _{eff}	i _{y,brutto}	N _{cR}	W _{min}	Z _{max}	W _{max}	V _R	R _{Rd,A}	R _{Rd,B,60}	R _{Rd,B,200}
mm	kg/m ²	cm ⁴ /m	cm ² /m		cm	kN/m	cm ³ /m	mm	cm ³ /m	kN/m			
0.70	11.43	467.82	14.56	6.13	5.67	196.19	44.45	84.41	53.19	32.47	6.36	22.25	35.54
0.75	12.25	501.24	15.60	6.87	5.67	219.74	49.35	84.09	58.56	39.51	7.39	25.66	40.85
0.80	12.92	534.65	16.46	7.63	5.70	244.13	53.44	83.91	63.12	47.48	8.53	29.42	46.68
0.88	14.37	588.12	18.31	8.90	5.67	284.74	60.64	83.65	71.15	62.31	10.57	36.10	56.97
0.90	14.70	601.48	18.72	9.21	5.67	294.59	62.42	83.59	73.12	66.44	11.12	37.88	59.71
1.00	16.33	668.31	20.80	10.62	5.67	339.84	71.55	83.32	83.22	89.78	14.20	47.84	74.96
1.15	18.78	768.56	23.92	12.82	5.67	410.30	85.63	82.99	98.75	133.97	19.84	65.84	102.33
1.25	20.41	835.39	26.00	14.46	5.67	462.69	95.28	82.90	109.63	170.17	23.70	77.94	120.55
1.50	24.50	1002.47	31.20	19.18	5.67	613.79	120.22	82.41	136.57	251.00	34.14	110.05	168.34